## PRODUCT INFORMATION PACKET



Model No: 056T17D11048 Catalog No: G244A 1,1725,DP,56C,3/60/575 Open Drip Proof (ODP)



Regal and Marathon are trademarks of Regal Beloit Corporation or one of its affiliated companies.

©2018 Regal Beloit Corporation, All Rights Reserved. MC017097E





## **Nameplate Specifications**

Output HP	1 Hp	Output KW	0.75 kW
Frequency	60 Hz	Voltage	575 V
Current	1.2 A	Speed	1725 rpm
Service Factor	1.15	Phase	3
Efficiency	83.5 %	Duty	Continous
Insulation Class	В	Design Code	В
KVA Code	М	Frame	56C
Enclosure	Drip Proof	Overload Protector	No
Ambient Temperature	40 °C	Drive End Bearing Size	6203
Opp Drive End Bearing Size	6203	UL	Recognized
CSA	Υ	CE	Υ
IP Code	22		

## **Technical Specifications**

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	4	Rotation	Reversible
Mounting	Round	Motor Orientation	Horizontal
Drive End Bearing	Ball	Opp Drive End Bearing	Ball
Frame Material	Rolled Steel	Shaft Type	Т
Overall Length	11.93 in	Shaft Diameter	0.625 in
Shaft Extension	1.88 in	Assembly/Box Mounting	F1 Out ODE Brkt Radial

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created: 06/29/2018