
PRODUCT INFORMATION PACKET



Model No: D473 Catalog No: D473

Refrigeration Motor, 1/20 HP, 1 Ph, 60 Hz, 115 V, 1550 RPM, 1 Speed, 3.3" Diameter, OAO









Nameplate Specifications

Service Factor1Phase1DutyAir OverInsulation ClassBFrame3.3EnclosureOpen AThermal ProtectionThermally ProtectedAmbient Temperature40 °CULRecognizedCSAY	Output HP	1/20 Hp	Output KW	0.04 kW	
Service Factor 1 Phase 1 Duty Air Over Insulation Class B Frame 3.3 Enclosure Open A Thermal Protection Thermally Protected Ambient Temperature 40 °C UL Recognized CSA Y	Frequency	60 Hz	Voltage	115 V	
DutyAir OverInsulation ClassBFrame3.3EnclosureOpen AThermal ProtectionThermally ProtectedAmbient Temperature40 °CULRecognizedCSAY	Current	2.00 A	Speed	1550 rpm	
Frame 3.3 Enclosure Open A Thermal Protection Thermally Protected Ambient Temperature 40 °C UL Recognized CSA Y	Service Factor	1	Phase	1	
Thermal Protection Thermally Protected Ambient Temperature 40 °C UL Recognized CSA Y	Duty	Air Over	Insulation Class	В	
UL Recognized CSA Y	Frame	3.3	Enclosure	Open Air Over	
<u> </u>	Thermal Protection	Thermally Protected	Ambient Temperature	40 °C	
CC Number of Speeds 4	UL	Recognized	CSA	Υ	
CE Number of Speeds	CE	N	Number of Speeds	1	

Technical Specifications

Electrical Type	Shaded Pole	Starting Method	Across The Line
Poles	4	Rotation	Counterclockwise Shaft End
Mounting	Extended Studs	Drive End Bearing	Sleeve
Opp Drive End Bearing	Sleeve	Frame Material	Steel
Shaft Type	Flat & Groove	Overall Length	7.37 in
Frame Length	2.95 in	Shaft Diameter	0.313 in
Shaft Extension	2.65 in		
Outline Drawing	7163815316_S001	Connection Drawing	NA

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:11/29/2022