
PRODUCT INFORMATION PACKET

Model No: 254TTDX4340 Catalog No: U208 15 HP Close-Coupled Pump Motor, 3 phase, 1800 RPM, 575 V, 254JP Frame, ODP **Close-Coupled Pump Motors**





marathon[®]

Motors





Product Information Packet: Model No: 254TTDX4340, Catalog No:U208 15 HP Close-Coupled Pump Motor, 3 phase, 1800 RPM, 575 V, 254JP Frame, ODP

marathon[®]

Nameplate Specifications

Output HP	15 Hp	Output KW	11.2 kW
Frequency	60 Hz	Voltage	575 V
Current	15.4 A	Speed	1760 rpm
Service Factor	1.15	Phase	3
Efficiency	91 %	Power Factor	80.2
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	G
Frame	254JP	Enclosure	Drip Proof
Thermal Protection	No	Ambient Temperature	40 °C
Drive End Bearing Size	6309	Opp Drive End Bearing Size	6208
UL	Recognized	CSA	Y
CE	Υ	IP Code	12
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	4	Rotation	Reversible
Resistance Main	.62 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel
Shaft Type	JP	Overall Length	27.04 in
Frame Length	15.15 in	Shaft Diameter	1.250 in
Shaft Extension	8.15 in	Assembly/Box Mounting	F1 ONLY
Connection Drawing	A-EE7300	Outline Drawing	A-SS86519-1515

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/12/2021

