## PRODUCT INFORMATION PACKET



Model No: 324TTDP4033
Catalog No: U239
40 HP Close-Coupled Pump Motor, 3 phase, 1800 RPM, 575 V, 324JP Frame, ODP
Close-Coupled Pump Motors



Product Information Packet: Model No: 324TTDP4033, Catalog No:U239 40 HP Close-Coupled Pump Motor, 3 phase, 1800 RPM, 575 V, 324JP Frame, ODP



## Nameplate Specifications

Output HP	40 Hp	Output KW	30.0 kW
Frequency	60 Hz	Voltage	575 V
Current	39.0 A	Speed	1770 rpm
Service Factor	1.15	Phase	3
Efficiency	93 %	Power Factor	82.5
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	F
Frame	324JP	Enclosure	Drip Proof
Thermal Protection	No	Ambient Temperature	40 °C
Drive End Bearing Size	312	Opp Drive End Bearing Size	311
UL	Recognized	CSA	Υ
CE	Υ	IP Code	23
Number of Speeds	1		

## **Technical Specifications**

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	4	Rotation	Reversible
Resistance Main	.165 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	JP	Overall Length	29.12 in
Frame Length	13.62 in	Shaft Diameter	1.250 in
Shaft Extension	8.12 in	Assembly/Box Mounting	F1/F2 CAPABLE
Connection Drawing	A-EE7300	Outline Drawing	B-SS200378-1362

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/12/2021



