## PRODUCT INFORMATION PACKET

Model No: 405UTFS4086
Catalog No: P474
Automotive Duty Motor, 50 HP, 3 Ph, 60 Hz, 460 V, 1200 RPM, 405U Frame, TEFC



Product Information Packet: Model No: 405UTFS4086, Catalog No:P474 Automotive Duty Motor, 50 HP, 3 Ph, 60 Hz, 460 V, 1200 RPM, 405U Frame, TEFC


## Nameplate Specifications

50 Hp	Output KW	37.3 kW			
60 Hz	Voltage	460 V			
60.0 A	Speed	1185 rpm			
1	Phase	3			
94.1 %	Power Factor	84			
Continuous	Insulation Class	F			
В	KVA Code	G			
405U	Enclosure	Totally Enclosed Fan Cooled			
No Protection	Ambient Temperature	65 °C			
6316	Opp Drive End Bearing Size	6313			
No	CSA	Υ			
Υ	IP Code	43			
1					
	60 Hz 60.0 A 1 94.1 % Continuous B 405U No Protection 6316 No	60 Hz Voltage 60.0 A Speed 1 Phase 94.1 % Power Factor Continuous Insulation Class B KVA Code 405U Enclosure No Protection Ambient Temperature 6316 Opp Drive End Bearing Size No CSA			

## **Technical Specifications**

Electrical Type Squirrel Cage Induction Run		Starting Method	Across The Line			
Poles	6	Rotation	Reversible			
Resistance Main	.142 Ohms	Mounting	Rigid Base			
Motor Orientation	Horizontal	Drive End Bearing	Ball			
Opp Drive End Bearing	Ball	Frame Material	Cast Iron			
Shaft Type	U	Assembly/Box Mounting	F1/F2 CAPABLE			
Outline Drawing	B-SS514649-1675	Connection Drawing	A-EE7300			

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:09/07/2022



- 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
- 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.

3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	В	С	2F	BS
1525	404U	14.75	35.50	12.25	6.12
1675	405U	16.25	37.00	13.75	6.88

, _												
( [						TOL UNLES	ERANCES S SPECIFIED			DRAWN	DJK 11-15	-1993
Γ						DEC.	INCHES	((O))  <u>  ~ L^\L\\\\</u>		СНК	ML 11-16-	-1993
	3	REDRAWN IN AUTOCAD	TAT 05-19-2	005	ML	.x	±.1			APPD	TB 11-16-	-1993
	2	UPDATED FRAME, CONDUIT BOX, AND ADDED 405				.xx	±.03	TITLE OUTLINE			3=16	,
		FRAME INFO. CN 27430, MU36657	KL 03-29-2	001		.xxx	±.005	400U FR. — TEFC — TAPPED LEAD HOLE			REF	
Γ	1	NEW DRAWING 4096513	DJK 11-17-19	93		.xxxx	±.0005	MAT'L.			FMF	
Γ	NO.	REVISION	BY & DAT	: [	CHK	ANG	±7'30"	FINISH			PREV	
Γ	IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED				141 JAD 1142 3331 TOT3			DRAWING NO			REV.	
				DIST WA B SS				B   SS5	514649   3		3	

(B-SS504887)

ERROR: syntaxerror
OFFENDING COMMAND: --nostringval-STACK:

/RS
-dictionary/Pscript\_WinNT\_Compat
-dictionary-

